



Mun Hean Singapore Pte Ltd
Mun Hean Industrial Building
51 Kim Keat Road. #05-02
Singapore 328821.
Tel: +65-62500522
Fax: +65-62536885
Email: poh.mt@munhean.com.sg

MFO-Series



Model Specifications

Spec. Item No.	RATIO	ACCURACY	CAPACITY	VOLTAGE MAX.	FREQUENCY	CONDUCTOR THROUGH	BAR SIZE MAX.	ROUND CONDUCTOR CROSS SECTION MAX.
MFO-20	30/5A~250/5A	CLASS:0.5	5 VA	AC. 600V	50/60 HZ	• 50/5A:2T • 100/5A~3000/5A 1T		
MFO-30	50/5A~300/5A	• 50/5A~100/5A CLASS:1 • 150/5A~3000/5A CLASS:0.5	• 50/5A:2.5 VA • 100/5A:2.5 VA				30X10mm	Ø 20mm
MFO-40	150/5A~600/5A		• 150/5A~400/5A 5VA				40X10mm	Ø 30mm
MFO-60	400/5A~1000/5A		• 500/5A~800/5A 10VA				60X20mm	Ø 40mm
MFO-100	800/5A~3000/5A		• 1000/5A~3000/5A 15VA				100X10mm	Ø 60mm

Dimension

Item No.	Size												
	A	B	C	D	E	F	G	H	I	J	K	L	
MFO-20	x	x	x	x	x	x	x	x	86	103	47.5	30	15
MFO-30	21	31	21	x	11.4	x	21	x	82	98	42.4	x	x
MFO-40	x	42	34	21.7	11	x	16	x	82	98	42.4	x	x
MFO-60	x	61	51	x	20.8	46	23	x	111	127	44	x	x
MFO-100	82	101	81.4	62	11	62	32	37	139	150	44.5	x	x

Technical drawing of the MFO-Series current transformer. The drawing includes a front view and a side view. The front view shows a central circular core with four terminals labeled A, B, C, and D. Dimensions A through L are indicated. The side view shows the transformer's profile with dimensions J, K, and L. A screw M8X20 is shown at the top.



Distributor: